

COMMERCIAL AND HEAVY DUTY TIRE APPLICATIONS

These heavy duty product applications show the best choices for most tires. Truck tires can vary in size due to tire manufacturers, tread design or recapping. SCC strongly recommends that traction products be fitted to the tire before actual use.

Chain laws can vary from state to state. Please refer to pages 22 & 23 for information on tire chain regulations. Product stock number shown in **red bold** will meet or exceed S.A.E. Class "S" clearance requirement. **Super Z8 recommended for commercial vehicles under 20,000 GVW.** * Indicates tire chain that is available in both CAM and non-CAM version. **The most popular version is shown.**

	TIRE SIZE	AXLE TYPE	SUPER Z [®]	SUPER Z8 [®]	ALLOY RADIAL CHAIN [®]	QUIK GRIP SQ. ROD ALLOY	DIAMOND BLUE ALLOY	QUIK GRIP LINK STYLE	QUIK GRIP V-BAR	QUIK GRIP V-BAR CTO
6.50	6.50-16C	Single	-	-	-	-	-	QG2219*	QG2819*	-
		Dual	-	-	-	-	-	QG4219*	QG4819	-
7	7.00-20	Single	-	SZ497	-	-	-	QG2214*	QG2814	-
	7-22.5	Single	ZT751	-	-	-	-	QG2214*	QG2814	QGV320
7.2	7.2-24	Single	-	-	-	-	-	QG0832	-	-
7.50	7.50-20	Single	-	-	-	-	-	QG2237	QG2837	-
		Dual	ZT956	-	-	-	-	-	QG4837	-
	7.50-22.5	Single	ZT865	-	-	-	-	QG2239CAM*	QG2839*	-
		Dual	ZT962	-	-	-	-	QG4239CAM*	QG4839	-
8	8-17.5	Single	ZT735	-	-	-	-	QG2219*	QG2819*	QGV315
		Dual	-	-	-	-	-	QG4219*	QG4819	-
	8-22.5	Single	-	-	-	-	-	QG2237	QG2837	-
		Dual	ZT956	-	-	-	-	-	QG4837	-
8.25	8.25-15TR	Single	ZT835	SZ462	-	QG2128	-	QG2228*	QG2828	-
		Dual	-	-	-	-	-	QG4228CAM	QG4828	-
	8.25-20	Single	ZT859	SZ492	TA1939	-	-	QG2239CAM*	QG2839*	-
		Dual	ZT962	-	TA3939	-	-	QG4239CAM*	QG4839	-
8.25-22.5	Single	ZT865	-	-	-	-	QG2239CAM*	QG2839*	-	
	Dual	ZT962	-	-	-	-	QG4239CAM*	QG4839	-	
8.3	8.3-24	Single	-	-	-	-	QG0822	-	-	
9.0	9.00-15TR	Single	ZT837	SZ468	-	-	-	-	-	-
		Dual	ZT948	-	-	-	-	-	-	-
	9.00-20	Single	ZT869	-	TA1941	-	DB2141	QG2241CAM*	QG2841*	-
		Dual	ZT970	-	TA3941	-	-	QG4241CAM*	QG4841	-
9-22.5	Single	ZT859	SZ492	TA1939	-	-	QG2239CAM*	QG2839*	-	
	Dual	ZT962	-	TA3939	-	-	QG4239CAM*	QG4839	-	
9.5	9.5-24	Single	-	-	-	-	-	QG0832	-	-
	9.5-28	Single	-	-	-	-	-	QG0836	-	-
	9.5-32	Single	-	-	-	-	-	QG0838	-	-
	9.5-38	Single	-	-	-	-	-	QG0862	-	-
	9.5-42	Single	-	-	-	-	-	QG0862	-	-
10.00	10.00-15TR	Single	ZT853	SZ486	-	-	-	-	-	-
		Dual	ZT956	-	-	-	-	-	-	-
	10.00-20	Single	ZT881	-	TA1945	QG2145	DB2145	QG2245CAM*	QG2845*	QGV343HD*
		Dual	ZT982	-	TA3945	QG4145	-	QG4245CAM*	QG4845*	QGV743HD*
	10.00-22	Single	ZT887	-	TA1949	QG2149	DB2149	QG2249CAM*	QG2849*	QGV344HD*
		Dual	ZT990	-	TA3949	QG4149	-	QG4249CAM*	QG4849*	QGV744HD*
10-22.5	Single	ZT869	-	TA1941	-	DB2141	QG2241CAM*	QG2841*	-	
	Dual	ZT970	-	TA3941	-	-	QG4241CAM*	QG4841	-	
10.00/90-20	Single	ZT877	-	-	QG2145	DB2145	QG2245CAM*	QG2845*	-	
	Dual	ZT970	-	-	QG4145	-	QG4245CAM*	QG4845*	-	
11	11.00-20	Single	ZT887	-	TA1951	QG2151	DB2151	QG2251CAM*	QG2851*	QGV355
		Dual	ZT990	-	TA3949	-	-	-	QG4851	QGV755
	11.00-22	Single	ZT891	-	-	QG2155	-	QG2255CAM*	QG2855*	QGV356
		Dual	-	-	-	-	-	-	QG4855	QGV756
	11-22.5	Single	ZT881	-	TA1945	QG2145	DB2145	QG2245CAM*	QG2845*	QGV343HD*
Dual		ZT982	-	TA3945	QG4145	-	QG4245CAM*	QG4845*	QGV743HD*	
11.00-24	Single	ZT891	-	-	-	-	-	QG2853	-	
11-24.5	Single	ZT887	-	TA1949	QG2149	DB2149	QG2249CAM*	QG2849*	QGV344HD*	
	Dual	ZT990	-	TA3949	QG4149	-	QG4249CAM*	QG4849*	QGV744HD*	
11.2	11.2-24	Single	ZT887	-	-	-	-	QG0836	-	-
	11.2-30	Single	-	-	-	-	-	QG0838	-	-
	11.2-32	Single	-	-	-	-	-	QG0856	-	-
	11.2-38	Single	-	-	-	-	-	QG0862	-	-

NOTE: FOR TIGHTENER RECOMMENDATIONS SEE PAGE 24

COMMERCIAL AND HEAVY DUTY TIRE APPLICATIONS

These heavy duty product applications show the best choices for most tires. Truck tires can vary in size due to tire manufacturers, tread design or recapping. SCC strongly recommends that traction products be fitted to the tire before actual use.

Chain laws can vary from state to state. Please refer to pages 22 & 23 for information on tire chain regulations. Product stock number shown in **red bold** will meet or exceed S.A.E. Class "S" clearance requirement. **Super Z8 recommended for commercial vehicles under 20,000 GVW.** * Indicates tire chain that is available in both CAM and non-CAM version. **The most popular version is shown.**

	TIRE SIZE	AXLE TYPE	SUPER Z®	SUPER Z8®	ALLOY RADIAL CHAIN®	QUIK GRIP SQ. ROD ALLOY	DIAMOND BLUE ALLOY	QUIK GRIP LINK STYLE	QUIK GRIP V-BAR	QUIK GRIP V-BAR CTO
11.5	11.50-20	Single	ZT887	-	TA1951	QG2151	DB2151	QG2251CAM*	QG2851*	QGV355
		Dual	ZT990	-	TA3949	-	-	-	QG4851	QGV755
	11.5-22.5	Single	ZT881	-	TA1947	-	-	QG2235	-	QGVC344HD*
		Dual	-	-	TA3947	-	-	-	-	QGVC744HD*
12.00	12.00-20	Single	ZT891	-	-	QG2155	-	QG2255CAM*	QG2855*	QGV356
		Dual	-	-	-	-	-	-	QG4855	QGV756
	12-22.5	Single	ZT887	-	TA1951	QG2151	DB2151	QG2251CAM*	QG2851*	QGV355
		Dual	ZT990	-	TA3949	-	-	-	QG4851	QGV755
	12.00-24	Single	-	-	-	-	-	QG2257	QG2857	-
	12-24.5	Single	-	-	-	QG2155	-	QG2255CAM*	QG2855*	QGV356
	Dual	-	-	-	-	-	-	QG4855	QGV756	
12.2	12.2-24	Single	-	-	-	-	-	QG0852	-	-
12.4	12.4-16	Single	-	-	-	-	-	QG0850	-	-
	12.4-24	Single	-	-	-	-	-	QG0852	-	-
	12.4-28	Single	-	-	-	-	-	QG0856	-	-
	12.4-32	Single	ZT-132	-	-	-	-	QG2615	-	-
	12.4-38	Single	-	-	-	-	-	QG0862	-	-
	12.4-42	Single	-	-	-	-	-	QG0866	-	-
12.5	12.5-22.5	Single	ZT887	-	TA1951	QG2151	DB2151	QG2251CAM*	QG2851*	QGV355
		Dual	ZT990	-	TA3949	-	-	-	QG4851	QGV755
	12.5-24.5	Single	ZT891	-	-	QG2155	-	QG2255CAM*	QG2855*	-
	Dual	-	-	-	-	-	-	QG4855	-	
	12.5/80-18	Single	-	-	-	-	-	QG0834	-	-
12.75	12.75-22.5	Single	ZT891	-	TA1949	QG2155	-	QG2255CAM*	QG2855*	-
		Dual	ZT990	-	TA3949	-	-	-	QG4855	-
13.00	13-22.5	Single	ZT891	-	-	-	-	-	-	-
	13.00-24	Single	-	-	-	-	-	QG2612	-	-
	13.00-25	Single	-	-	-	-	-	QG2612	-	-
	13/80-20	Single	-	-	TA1945	QG2145	DB2145	QG2245CAM*	QG2845*	-
	Dual	-	-	TA3945	QG4145	-	QG4245CAM*	QG4845*	-	
13.50	13.50-16.1	Single	-	-	-	-	QG0838	-	-	
13.6	13.6-16	Single	-	-	-	-	-	QG0850	-	-
	13.6-26	Single	-	-	-	-	-	QG0858	-	-
	13.6-28	Single	-	-	-	-	-	QG0859	-	-
	13.6-38	Single	-	-	-	-	-	QG0866	-	-
13.9	13.9-36	Single	-	-	-	-	QG0866	-	-	
14.00	14-17.5	Single	-	-	-	-	-	QG0850	-	-
	14.00-20 GRADER	Single	ZT-132	-	-	-	-	QG2612	-	-
	14.00-21	Single	-	-	-	-	-	QG2612	-	-
	14.00-24 GRADER	Single	ZT-132	-	-	-	-	QG2615	-	-
	14.00-25	Single	-	-	-	-	-	QG2615	-	-
	14/80-20	Single	ZT892	-	-	QG2155	-	QG2255CAM*	QG2855*	-
	Dual	-	-	-	-	-	-	QG4855	-	
14.9	14.9-24	Single	-	-	-	-	-	QG0859	-	-
	14.9-26	Single	ZT-132	-	-	-	-	QG2615	-	-
	14.9-28	Single	-	-	-	-	-	QG0869	-	-
	14.9-30	Single	-	-	-	-	-	QG0876	-	-
15	15-22.5	Single	-	-	-	-	QG3255	-	-	
15.5	15.5-25	Single	ZT-132	-	-	-	QG2612	-	-	
16.00	16.00-20 GRADER	Single	ZT-141	-	-	-	-	QG2624	-	-
	16.00-21 GRADER	Single	ZT-141	-	-	-	-	QG2624	-	-
	16.00-24 GRADER	Single	ZT-143	-	-	-	-	QG2627	-	-
	16.00-25 GRADER	Single	ZT-143	-	-	-	-	QG2627	-	-
16.5	16.5-19.5	Single	-	-	-	-	-	QG3255	-	-
	16.5-22.5	Single	ZT896	-	TA2071	-	-	-	-	-

NOTE: FOR TIGHTENER RECOMMENDATIONS SEE PAGE 24

COMMERCIAL AND HEAVY DUTY TIRE APPLICATIONS

* Indicates tire chain that is available in both CAM and non-CAM version. The most popular version is shown.

	TIRE SIZE	AXLE TYPE	SUPER Z®	SUPER Z8®	ALLOY RADIAL CHAIN®	QUIK GRIP SQ. ROD ALLOY	DIAMOND BLUE ALLOY	QUIK GRIP LINK STYLE	QUIK GRIP V-BAR	QUIK GRIP V-BAR CTO
16.9	16.9-20	Single	-	-	-	-	-	QG2612	-	-
	16.9-24	Single	-	-	-	-	-	QG0874	-	-
	16.9-28	Single	-	-	-	-	-	QG0876	-	-
	16.9-30	Single	-	-	-	-	-	QG0877	-	-
	16.9-34	Single	-	-	-	-	-	QG0879	-	-
	16.9-38	Single	-	-	-	-	-	QG0880	-	-
17.5	17.5L-24	Single	-	-	-	-	-	QG0874	-	-
	17.5-25	Single	-	-	-	-	-	QG2624	-	-
18.00	18.00-24	Single	-	-	-	-	-	QG2636	-	-
	18.00-25	Single	ZT-145	-	-	-	-	QG2636	-	-
	18.00-26	Single	-	-	-	-	-	QG2636	-	-
18.4	18.4-16.1	Single	-	-	-	-	-	QG0881	-	-
	18.4-26	Single	-	-	-	-	-	QG0883	-	-
	18.4-30	Single	-	-	-	-	-	QG0885	-	-
	18.4-34	Single	-	-	-	-	-	QG0887	-	-
	18.4-38	Single	-	-	-	-	-	QG0889	-	-
19	19-22.5	Single	-	-	-	-	-	QG3261	-	-
19.5	19.5-19.5	Single	-	-	-	-	-	QG3261	-	-
	19.5L-24	Single	-	-	-	-	-	QG0883	-	-
20.5	20.5-25	Single	-	-	-	-	-	QG2633	-	-
21	21L-24	Single	-	-	-	-	-	QG2648	-	-
	21.00-25	Single	-	-	-	-	-	QG2648	-	-
21.5	21.5-16	Single	-	-	-	-	-	QG0882	-	-
	21.5L-16.1	Single	-	-	-	-	-	QG0882	-	-
23.1	23.1-26	Single	-	-	-	-	-	QG0891	-	-
	23.1-30	Single	-	-	-	-	-	QG0893	-	-
23.5	23.5-25	Single	-	-	-	-	-	QG2645	-	-
37	37x12.50-17	Single	ZT859	SZ492	-	-	-	QG3235	-	-
	37x12.50-20LT	Single	ZT859	SZ492	-	-	-	QG3235	-	-
38	38x14.50-17	Single	ZT881	-	-	-	-	QG3235	-	-
	38x15-15	Single	ZT881	-	-	-	-	QG3235	-	-
	38x10.50-15	Single	ZT859	SZ492	-	-	-	QG2239CAM*	QG2839*	-
215	215/75-17.5	Single	ZT729	-	-	QG2121	-	QG2221*	QG2821*	QGV315
		Dual	-	-	-	-	-	QG4221*	QG4821*	-
	215/75-19.5	Single	ZT747	-	-	QG2128	-	QG2228*	QG2828*	QGV320
	Dual	-	-	-	-	-	QG4228CAM	QG4828	-	
225	225/70-19.5	Single	ZT741	-	-	QG2121	-	QG2221*	QG2821*	QGV320
		Dual	-	-	-	-	-	QG4221*	QG4821*	-
	225/70-22.5	Single	-	SZ497	-	-	-	QG2214*	QG2814	-
	225/75-17.5	Single	ZT735	-	-	QG2121	-	QG2221*	QG2821*	QGV315
		Dual	-	-	-	-	-	QG4221*	QG4821*	-
	225/75-19.5	Single	ZT747	-	-	QG2128	-	QG2228*	QG2828*	QGV320
	Dual	-	-	-	-	-	QG4228CAM	QG4828	-	
235	225/80-22.5	Single	-	-	-	-	-	QG2237	QG2837	-
		Dual	ZT956	-	-	-	-	-	QG4837	-
	235/70-17.5	Single	ZT735	-	-	QG2121	-	QG2221*	QG2821*	QGV320
		Dual	-	-	-	-	-	QG4221*	QG4821*	-
245	235/70-19.5	Single	ZT741	-	-	QG2121	-	QG2221*	QG2821*	QGV320
		Dual	-	-	-	-	-	QG4221*	QG4821*	-
	235/75-17.5	Single	ZT741	-	-	QG2128	-	QG2228	QG2828*	QGV320
		Dual	-	-	-	-	-	QG4228CAM	QG4828	-
245	235/80-22.5	Single	ZT859	SZ492	TA1939	-	-	QG2239CAM*	QG2839	-
		Dual	ZT956	-	TA3939	-	-	QG4239CAM*	QG4839	-
	245/70-17.5	Single	ZT741	-	-	QG2128	-	QG2228*	QG2828*	QGV320
		Dual	-	-	-	-	-	QG4228CAM	QG4828	-
	245/70-19.5	Single	ZT835	SZ462	-	QG2128	-	QG2228*	QG2828*	-
		Dual	-	-	-	-	-	QG4228CAM	QG4828	-
245	245/70-22.5	Single	ZT853	SZ486	-	-	-	QG2237	QG2837	-
		Dual	-	-	-	-	-	-	QG4837	-
	245/75-17.5	Single	ZT741	-	-	QG2128	-	QG2228*	QG2828*	QGV320
		Dual	-	-	-	-	-	QG4228CAM	QG4828	-

NOTE: FOR TIGHTENER RECOMMENDATIONS SEE PAGE 24

COMMERCIAL AND HEAVY DUTY TIRE APPLICATIONS

These heavy duty product applications show the best choices for most tires. Truck tires can vary in size due to tire manufacturers, tread design or recapping. SCC strongly recommends that traction products be fitted to the tire before actual use.

Chain laws can vary from state to state. Please refer to pages 22 & 23 for information on tire chain regulations. Product stock number shown in **red bold** will meet or exceed S.A.E. Class "S" clearance requirement. **Super Z8 recommended for commercial vehicles under 20,000 GVW.** * Indicates tire chain that is available in both CAM and non-CAM version. The most popular version is shown.

	TIRE SIZE	AXLE TYPE	SUPER Z®	SUPER Z8®	ALLOY RADIAL CHAIN®	QUIK GRIP SQ. ROD ALLOY	DIAMOND BLUE ALLOY	QUIK GRIP LINK STYLE	QUIK GRIP V-BAR	QUIK GRIP V-BAR CTO
245	245/75-19.5	Single Dual	ZT835 -	SZ462 -	- -	QG2128 -	- -	QG2228* QG4228CAM	QG2828* QG4828	- -
	245/75-22.5	Single Dual	ZT859 ZT956	SZ492 -	- -	- -	- -	QG2239CAM* QG4239CAM*	QG2839* QG4839	- -
	245/80-22.5	Single Dual	ZT859 ZT956	SZ492 -	TA1939 TA3939	- -	- -	QG2239CAM* QG4239CAM*	QG2839* QG4839	- -
255	255/60-22.5	Single Dual	ZT837 -	SZ468 -	- -	- -	- -	QG2237 -	QG2837 QG4837	- -
	255/70-19.5	Single Dual	ZT835 -	SZ462 -	- -	QG2128 -	- -	QG2228* QG4228CAM	QG2828* QG4828	- -
	255/70-22.5	Single Dual	ZT859 ZT956	SZ497 -	TA1939 TA3939	- -	- -	QG2239CAM* QG4239CAM*	QG2839* QG4839	- -
	255/75-22.5	Single Dual	ZT859 ZT956	SZ492 -	TA1939 TA3939	- -	- -	QG2239CAM* QG4239CAM*	QG2839* QG4839	- -
	255/80-22.5	Single Dual	ZT865 ZT962	- -	- -	- -	- -	QG2239CAM* QG4239CAM*	QG2839* QG4839	- -
265	265/70-19.5	Single Dual	ZT837 -	SZ468 -	- -	- -	- -	QG2237 -	QG2837 QG4837	- -
	265/70-22.5	Single Dual	ZT869 ZT956	- -	- -	- -	- -	QG2239CAM* QG4239CAM*	QG2839* QG4839	- -
	265/75-19.5	Single Dual	ZT837 ZT948	SZ497 -	- -	- -	- -	QG2237 -	QG2837 QG4837	- -
	265/75-22.5	Single Dual	ZT865 ZT962	- -	- -	- -	- -	QG2239CAM* QG4239CAM*	QG2839* QG4839	- -
275	275/70-19.5	Single Dual	ZT837 ZT948	SZ497 -	- -	- -	- -	QG2237 -	QG2837 QG4837	- -
	275/70-22.5	Single Dual	ZT869 ZT956	- -	- -	- -	- -	QG2239CAM* QG4239CAM*	QG2839* QG4839	- -
	275/75-22.5	Single Dual	ZT877 ZT962	- -	TA1943 TA3943	QG2143 QG4143	DB2143 -	QG2243CAM* QG4243CAM*	QG2843CAM QG4843CAM	QGV343HD* QGV743HD*
	275/80-22.5	Single Dual	ZT881 ZT970	- -	TA1943 TA3943	QG2143 QG4143	DB2143 -	QG2243CAM* QG4243CAM*	QG2843CAM QG4843CAM	QGV343HD* QGV743HD*
	275/80-24.5	Single Dual	ZT881 ZT982	- -	TA1947 TA3947	QG2147 QG4147	DB2147 -	QG2247CAM* QG4247CAM*	QG2847CAM QG4847CAM	QGV344HD* QGV744HD*
285	285/65-22.5	Single Dual	ZT869 ZT956	- -	- -	- -	- -	QG2239CAM* QG4239CAM*	QG2839* QG4839	- -
	285/70-19.5	Single Dual	ZT853 ZT948	SZ486 -	- -	- -	- -	QG2234CAM -	- -	- -
	285/70-24.5	Single Dual	ZT881 ZT970	- -	TA1943 TA3943	QG2145 QG4145	DB2145 -	QG2245CAM* QG4245CAM*	QG2845* QG4845*	- -
	285/75-22.5	Single Dual	ZT877 ZT962	- -	TA1943 TA3943	QG2143 QG4143	DB2143 -	QG2243CAM* QG4243CAM*	QG2843CAM QG4843CAM	QGV343HD* QGV743HD*
	285/75-24.5	Single Dual	ZT881 ZT982	- -	TA1947 TA3947	QG2147 QG4147	DB2147 -	QG2247CAM* QG4247CAM*	QG2847CAM QG4847CAM	QGV344HD* QGV744HD*
	285/80-22.5	Single Dual	ZT881 ZT982	- -	TA1951 -	QG2151 -	DB2151 -	QG2251CAM* -	QG2851* QG4851	- -
	285/80-24.5	Single Dual	ZT881 ZT982	- -	TA1951 TA3949	QG2151 -	DB2151 -	QG2251CAM* -	QG2851* QG4851	- -
	285/80-24.5	Single Dual	ZT881 ZT982	- -	TA1951 TA3949	QG2151 -	DB2151 -	QG2251CAM* -	QG2851* QG4851	- -
295	295/60-22.5	Single	ZT859	-	-	-	-	-	-	-
	295/70-19.5	Single	ZT853	SZ497	-	-	-	-	-	-
	295/70-22.5	Single Dual	ZT877 -	- -	TA1943 TA3943	QG2143 QG4143	DB2143 -	QG2243CAM* QG4243CAM*	QG2843CAM QG4843CAM	QGV343HD* QGV743HD*
	295/75-17.5	Single	ZT859	SZ492	-	-	-	QG2226	-	-
	295/75-22.5	Single Dual	ZT881 ZT970	- -	TA1943 TA3943	QG2143 QG4143	DB2143 -	QG2243CAM* QG4243CAM*	QG2843CAM QG4843CAM	- -

NOTE: FOR TIGHTENER RECOMMENDATIONS SEE PAGE 24

COMMERCIAL AND HEAVY DUTY TIRE APPLICATIONS

* Indicates tire chain that is available in both CAM and non-CAM version. The most popular version is shown.

TIRE SIZE	AXLE TYPE	SUPER Z®	SUPER Z8®	ALLOY RADIAL CHAIN®	QUIK GRIP SQ. ROD ALLOY	DIAMOND BLUE ALLOY	QUIK GRIP LINK STYLE	QUIK GRIP V-BAR	QUIK GRIP V-BAR CTO
295	295/75-24.5	Single	ZT881	-	TA1947	-	QG2235	-	QGV344HD*
	Dual	ZT982	-	TA3947	-	-	-	-	QGV344HD*
	295/80-22.5	Single	ZT881	-	TA1951	QG2151	DB2151	QG2251CAM*	QG2851*
	Dual	ZT982	-	-	-	-	-	QG4851	-
305	305/70-22.5	Single	ZT881	-	-	QG2145	DB2145	-	-
	Dual	-	-	-	-	QG4145	-	-	-
	305/75-24.5	Single	ZT887	-	-	QG2155	DB2151	QG2255CAM*	QG2855*
	Dual	ZT982	-	-	-	-	-	QG4855	-
	305/80-22.5	Single	ZT881	-	TA1947	QG2151	DB2151	QG2251CAM*	QG2851*
	Dual	ZT982	-	TA3947	-	-	-	QG4851	-
	305/85-22.5	Single	ZT892	-	-	QG2155	-	QG2255CAM*	QG2855*
	Dual	ZT990	-	-	-	-	-	QG4855	QGV355 QGV755
315	315/70-22.5	Single	ZT881	-	TA1945	QG2145	DB2145	-	QGV343HD*
	Dual	ZT970	-	TA3945	QG4145	-	-	-	QGV343HD*
	315/80-22.5	Single	ZT887	-	TA1949	QG2155	DB2151	QG2255CAM*	QG2855*
	Dual	ZT990	-	TA3949	-	-	-	QG4855	-
	315/80-22.5	Single	ZT891	-	TA1949	QG2155	DB2151	QG2255CAM*	QG2855*
	MICHELIN	Dual	-	-	TA3949	-	-	QG4855	-
	320	320/85-38	Single	-	-	-	-	QG0862	-
365	365/70-22.5	Single	ZT892	-	-	-	-	-	-
	365/80-20	Single	ZT892	-	-	QG2155	-	QG2255CAM*	QG2855*
	Dual	-	-	-	-	-	-	QG4855	-
	365/85-20	Single	-	-	-	-	QG3255	-	-
380	380/70-28	Single	-	-	-	-	QG2612	-	-
	380/80-38	Single	-	-	-	-	QG0879	-	-
	380/85-28	Single	-	-	-	-	QG0869	-	-
	380/85-30	Single	-	-	-	-	QG0876	-	-
	380/85-34	Single	-	-	-	-	QG0877	-	-
385	385/65-22.5	Single	ZT892	-	-	-	QG3255	-	-
	385/95-25	Single	ZT-132	-	-	-	QG2615	-	-
395	395/85-20	Single	ZT898	-	-	-	QG3261	-	-
400	400/70-20	Single	ZT892	-	-	-	QG3255	-	-
420	420/70-28	Single	-	-	-	-	QG0869	-	-
	420/85-28	Single	-	-	-	-	QG0876	-	-
	420/85-34	Single	-	-	-	-	QG0879	-	-
	420/90-30	Single	-	-	-	-	QG0879	-	-
425	425/55-22.5	Single	ZT896	-	TA2071	-	-	-	-
	425/65-22.5	Single	ZT896	-	TA2071	-	-	-	-
	425/70-22.5	Single	ZT898	-	TA2071	-	-	-	-
440	440/80-28	Single	-	-	-	-	QG0876	-	
445	445/50-22.5	Single	ZT897	-	TA2069	-	QG3269CAM*	-	-
	445/55-22.5	Single	-	-	-	-	QG3255	-	-
	445/65-19.5	Single	ZT896	-	TA2071	-	-	-	-
	445/65-22.5	Single	ZT-118	-	-	-	QG3261	-	-
	445/80-22.5	Single	-	-	-	-	QG0874	-	-
	445/95-25	Single	ZT-143	-	-	-	QG2627	-	-
455	455/50-22.5	Single	ZT897	-	TA2069	-	QG3269CAM*	-	-
	455/55-22.5	Single	ZT899	-	TA2069	-	QG3269CAM*	-	-
480	480/70-28	Single	-	-	-	-	QG0883	-	-
	480/70-30	Single	-	-	-	-	QG0883	-	-
	480/80-38	Single	-	-	-	-	QG0889	-	-
520	520/70-34	Single	ZT-145	-	-	-	QG2636	-	
540	540/60-30	Single	-	-	-	-	QG2633	-	
550	550/65-25	Single	-	-	-	-	QG0883	-	

NOTE: FOR TIGHTENER RECOMMENDATIONS SEE PAGE 24